

# Slap-N-Track

## Adaptable asset tracker

The Slap-N-Track is a powerful and versatile tracker, designed for customers who need to reliably monitor their assets no matter the situation or environment. The Slap-N-Track is highly configurable, allowing it to fit within any asset scenario. It provides periodic tracking, motion tracking and stolen asset tracking, and has a battery life that exceeds ten years during normal usage.


## Slap-N-Track Highlights

- RUGGED IP69K SEALED HOUSING
- TRI-COLOR LED FOR INSTALLER STATUS
- PUSH BUTTON FOR INSTALLER ACTIVATION & CONFIGURABLE RESET/POWER
- 10+ YEARS OF BATTERY LIFE
- PERIODIC STATIONARY & FREQUENT MOTION GPS LOCATION REPORTING
- REAL-TIME STOLEN ASSET DETECTION MODE
- EASY UPDATING VIA OTA FIRMWARE & CONFIGURATION
- FUTURE-PROOF INVESTMENT WITH 3GPP-APPROVED LTE-M & NB-IOT TECHNOLOGIES
- SECURE CONNECTION TO CLOUD TRACKING PLATFORM
- FLEXIBLE MOUNTING OPTIONS (ADHESIVE, SCREWS, ZIP TIES, MAGNETS)



### **Dimensions**







#### **GENERAL**

Communication Modes	LTE
Location Technology	GPS
Updates/Configuration	OTA
Status LEDs	1 Tri-color (Red, Amber, Green)

#### **CELLULAR**

Operating Bands	4G LTE CAT M1 / NB-IoT
Data Communication	MQTT, HTTPS, JSON, SMS
Antennas	Internal Cell/GPS

#### **GPS**

Location Technology	GNSS / GPS
Tracking Sensitivity	-155 dBm
Acquisition Sensitivity	-147 dBm
Position Accuracy	2.5m
Hot Start Acquisition	~1 Sec
Update Rate	1Hz

#### **PHYSICAL SPECIFICATION**

Dimensions	127 x 63 x 34 mm (5 x 2.5 x 1.3")
Weight	227 g (8 oz)
Mounting Options	Magnets, Zip Ties, Screws, Adhesive

#### **ELECTRICAL**

Battery Options	4 x AA (LiSOCl <sub>2</sub> )
	3 x CR123A (LiMnO <sub>2</sub> )

#### **ENVIRONMENTAL**

Operating Temperature	-40° to 85°C
Storage Temperature	-40° to 85°C
Humidity	90% RH @ 38°C
Shock & Vibration	SAE J1455
Dust & Water Ingress	IP69K Seal Rated, Level 1 & 2 Pressure Wash

#### CERTIFICATIONS

AT&T 4G LTE, PTCRB, FCC/IC, CISPR 25 Class 3, RoHS Compliant